



The all new FR3 Firerated Aluminium Enclosed Safety Switches are suitable for installations that require high durability. The switches are tested to withstand 300°C for 2 hours.

Conforming to EN-12101-3 Smoke and Heat Control Systems Standard.

Suitable for use in:

- Tunnels
- Car Parks
- Industrial Buildings
- Warehouses
- And other smoke and heat applications



F300 2H (FR3)

Up to 200 A

- IP66
- Padlockable
- Door interlock with defeat mechanism
- ON-locking facility as option
- Good corrosion and UV resistance
- Excellent for hard weather conditions

Type	AC-21	400 V	AC-22	400 V	AC-23	400 V	EAN code 6419410...	Enclosure	Weight kg
		415 V		415 V		415 V			
		690 V		690 V		415 V			
F300 2H	I _n / A		I _n / A	I _n / A	P / kW				
3 poles									
KEA 316U FR3	25 A		16 A	16 A	7.5 kW	...333396	A2	0.8	
KEA 325U FR3	40 A		25 A	25 A	11 kW	...333426	A2	0.8	
KEA 340U FR3	63 A		40 A	40 A	22 kW	...333457	A2	0.8	
KEA 363U FR3	80 A		63 A	40 A	22 kW	...333488	A3	2	
KEA 380U FR3	100 A		80 A	63 A	30 kW	...333518	A3	2	
KEA 3125 FR3	160 A		125 A	100 A	55 kW	...333549	A4	8.6	
KEA 3160 FR3	200 A		160 A	135 A	75 kW	...333556	A4	8.6	
KEA 3200C FR3	200 A		200 A*	200 A	110 kW	...333563	A4	8.6	
4 poles									
KEA 416U FR3	25 A		16 A	16 A	7.5 kW	...333402	A2	0.9	
KEA 425U FR3	40 A		25 A	25 A	11 kW	...333433	A2	0.9	
KEA 440U FR3	63 A		40 A	40 A	22 kW	...333464	A2	0.9	
KEA 463U FR3	80 A		63 A	40 A	22 kW	...333495	A3	2.1	
KEA 480U FR3	100 A		80 A	63 A	30 kW	...333525	A3	2.1	
KEA 4125 FR3	160 A		125 A	100 A	55 kW	...333570	A4	8.7	
KEA 4160 FR3	200 A		160 A	135 A	75 kW	...333587	A4	8.7	
KEA 4200C FR3	200 A		200 A*	200 A	110 kW	...333594	A4	8.7	
6 poles									
KEA 616U FR3	25 A		16 A	16 A	7.5 kW	...333419	A3	2.3	
KEA 625U FR3	40 A		25 A	25 A	11 kW	...333440	A3	2.3	
KEA 640U FR3	63 A		40 A	40 A	22 kW	...333471	A3	2.3	
KEA 663U FR3	80 A		63 A	40 A	22 kW	...333501	A3	2.3	
KEA 680U FR3	100 A		80 A	63 A	30 kW	...333532	A3	2.3	
KEA 6125 FR3	160 A		125 A	100 A	55 kW	...333600	A5	15	
KEA 6160 FR3	200 A		160 A	135 A	75 kW	...333617	A5	15	
KEA 6200C FR3	200 A		200 A*	200 A	110 kW	...333624	A5	15	
8 poles									
KEA 816U FR3	25 A		16 A	16 A	7.5 kW	...333631	A3	2.4	
KEA 825U FR3	40 A		25 A	25 A	11 kW	...333648	A3	2.4	
KEA 840U FR3	63 A		40 A	40 A	22 kW	...333655	A3	2.4	
KEA 863U FR3	80 A		63 A	40 A	22 kW	...333662	A3	2.4	
KEA 880U FR3	100 A		80 A	63 A	30 kW	...333679	A3	2.4	
* 400/415 V									

Data subject to change without notice



APS Industrial
apsindustrial.com.au
1300 309 303

KATKO OY
www.katko.com
info@katko.com