



KATKO Stainless Steel Product Range (KER) is designed for the needs of Food & Beverage and Mining industries. The AISI 304 and AISI 316 enclosures provide a high level of protection.

These high-quality enclosures were specifically designed to withstand chemicals and have as few cavities as possible in order to be easily cleanable.

UL-listed product. 

Suitable for use in:

- Food & Beverage industries
- Mining industry
- Hazardous and demanding environments



STAINLESS STEEL SAFETY SWITCHES

Up to 160 A

- Designed for hygienic and heavy environments
- Padlockable
- Easy to install and to keep clean
- Acid proof: AISI 316
- IP66
- Rainhood protection with angled top (RS)

Type		AC-22	400 V	AC-23		AC-23	690 V	EAN-Code 6419410...		Enclosure & handle		Weight kg	
			415 V		400 V								
			690 V		415 V								
R	RS	I _n / A	I _n / A	P / kW	I _n / A	P / kW	R	RS	R	RS	R	RS	
3 poles													
KER 316R	KER 316RS	16 A	16 A	7.5 kW	16 A	11 kW	...306550	...306611	H23T	H24T	1.2	1.7	
KER 325R	KER 325RS	25 A	25 A	11 kW	25 A	22 kW	...306567	...306628	H23T	H24T	1.2	1.7	
KER 340R	KER 340RS	40 A	40 A	22 kW	32 A	30 kW	...306574	...306635	H23T	H24T	1.2	1.7	
KER 363R	KER 363RS	63 A	40 A	22 kW	40 A	37 kW	...306703	...307052	H32T	H34T	2,3	2,9	
KER 380R	KER 380RS	80 A	63 A	30 kW	40 A	37 kW	...306710	...307069	H32T	H34T	2,3	2,9	
KER 3125R	KER 3125RS	125 A	100 A	55 kW	80 A	55 kW	...357828	...357835	H02T	H02TR	6,9	8	
KER 3160R	KER 3160RS	160 A	135 A	75 kW	125 A	90 kW	...357842	...357859	H02T	H02TR	6,9	8	
4 poles													
KER 416R	KER 416RS	16 A	16 A	7.5 kW	16 A	11 kW	...306581	...306642	H23T	H24T	1.3	1.8	
KER 425R	KER 425RS	25 A	25 A	11 kW	25 A	22 kW	...306598	...306659	H23T	H24T	1.3	1.8	
KER 440R	KER 440RS	40 A	40 A	22 kW	32 A	30 kW	...306604	...306666	H23T	H24T	1.3	1.8	
KER 463R	KER 463RS	63 A	40 A	22 kW	40 A	37 kW	...306727	...307076	H32T	H34T	2,4	3,0	
KER 480R	KER 480RS	80 A	63 A	30 kW	40 A	37 kW	...306734	...307083	H32T	H34T	2,4	3,0	
KER 4125R	KER 4125RS	125 A	100 A	55 kW	80 A	55 kW	...305720	...305737	H02T	H02TR	7	8,1	
KER 4160R	KER 4160RS	160 A	135 A	75 kW	125 A	90 kW	...305744	...305751	H02T	H02TR	7	8,1	