

RAMTIGHT

HISTORY OF APS INDUSTRIAL

APS Industrial was formed in 2018 incorporating the established businesses of Ramelec Pty Ltd and HiTech Control Systems Pty Ltd who shared in over 20 years of successfully servicing the electrical needs of customers in Australia.

Both existing partial distributors of Siemens products in Australia, together these two companies offered a wealth of experience and expertise when it came to bringing this world class range to the local market.

It was these existing footprints and exclusive distribution agreements that formed the ideal platform for APS Industrial to develop a complete portfolio and customer focused product and solution model that would change the landscape of the Australian industrial electrical industry.

First appointed as the master distributor of the Siemens range in Australia, APS Industrial then secured key complementary national distribution partnerships with a number of other leading global manufacturers led by Weidmüller, Rittal, EPCOS (a TDK Group company) and Katko. Bringing together this extensive technology portfolio, APS Industrial is now able to serve the local market as a connected technology partner intent on delivering quality products and the ultimate in customer service.

APS INDUSTRIAL YOUR GATEWAY TO INDUSTRIAL SUCCESS

At APS Industrial, we're the gateway that connects the world's leading industrial manufacturers to the local industry.

We're committed to offering our customers an experience that is consistent and reliable as we together create solutions that power Australia.

COMPETITIVE

Our desire to help our customers drives our competitive nature as we strive to ensure we collectively succeed.

COMMITTED

In all that we do, our commitment to our valued customers is our promise.

ADAPTIVE

Our expertise, experience and scale allows us to seamlessly adapt to your needs and industry trends.

SUPPORTING

Our job never ends and we pride ourselves on our full cycle service and support.







At APS Industrial, our purpose starts and ends with our customer's success and we continually develop our team to ensure we're best placed to serve their varied needs when they need us.

- System Integrators
- Switchboard Builders
- **Electrical Contractors**
- Machine Builders (OEMs)
- Consulting Engineers
- Wholesalers
- End Users



Bringing together a complete and quality range of products from leading global manufacturers, customers can be sure they will find what they are looking for when they deal with us.

- Automation & Process
- Power Distribution
- Motor Control & Drives
- Wiring Accessories & Control
- Power Quality



INDUSTRIES SERVED

At APS Industrial we understand the different challenges and drivers of the different industries we serve. Using our experience and knowledge we are able to tailor our service and solution offering to a range of primary industries.

- Manufacturing
- Construction & Building
- Water & Wastewater
- Food & Beverage
- Mining & Minerals Processing
- Infrastructure





RAMTIGHT

FLEXIBLE STEEL CONDUIT

Ramtight flexible steel conduit has been designed and manufactured to the highest standard ISO 9001:2008 and complies with AS/NZS 2053.8. This ensures you are getting a high quality product which is suitable for use in all arduous areas including industrial and hazardous areas.

Ramtight Flexible conduit is manufactured from a galvanised steel core with a nylon sealing core fitted between the spiral cores and is covered with a flexible flame retardant PVC jacket. Ramtight is also resistant to sun light and oil and has an IP66 rating when fitted with Ramtight nickel plated brass or steel fittings.

Ramtight's construction allows it to be very flexible and gives it the ability to both absorb vibration and continuous movement making it ideal to use on conveyors and automatic machinery or wherever heavy duty mechanical protection is required.



Standards: AS/NZS 2053.8

Galvanised steel core

Nylon sealing core fitted between the spiral cores

Flexible flame retardant PVC jacket

Oil resistant

IP66

Temperature range -10° to +105°C

| PART NO | DESCRIPTION | I.D. | O.D. | MIN BENDING RADIUS | PACK QTY |
|-----------|--------------------|---------|---------|-----------------------|----------|
| RT-1625-B | 16mm Black Conduit | 12.00mm | 18.00mm | 50mm | 25M |
| RT-2025-B | 20mm Black Conduit | 16.00mm | 21.30mm | 65mm | 25M |
| RT-2525-B | 25mm Black Conduit | 21.00mm | 26.70mm | 75mm | 25M |
| RT-3225-B | 32mm Black Conduit | 26.50mm | 33.40mm | 100mm | 25M |
| RT-4010-B | 40mm Black Conduit | 35.00mm | 42.20mm | 120mm | 10M |
| RT-5010-B | 50mm Black Conduit | 40.50mm | 48.72mm | 140mm | 10M |
| RT-6310-B | 63mm Black Conduit | 51.00mm | 61.30mm | 180mm | 10M |

NICKEL PLATED FITTINGS











Also available:

PG, BSP & NPT Fittings

STRAIGHT NICKEL PLATED BRASS FITTINGS



| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|-----------|-------------------------------|-------------|----------|
| RTF-16 | 16mm Straight Conduit Fitting | 16mm | 25 |
| RTF-16/20 | 16mm Straight Conduit Fitting | 20mm | 25 |
| RTF-20 | 20mm Straight Conduit Fitting | 20mm | 25 |
| RTF-25 | 25mm Straight Conduit Fitting | 25mm | 25 |
| RTF-32 | 32mm Straight Conduit Fitting | 32mm | 10 |
| RTF-40 | 40mm Straight Conduit Fitting | 40mm | 5 |
| RTF-50 | 50mm Straight Conduit Fitting | 50mm | 2 |
| RTF-63 | 63mm Straight Conduit Fitting | 63mm | 1 |

45° BRASS FITTINGS



| RTF-1645 | 16mm 45° Fitting | 16mm | 25 |
|----------|------------------|------|----|
| RTF-2045 | 20mm 45° Fitting | 20mm | 25 |
| RTF-2545 | 25mm 45° Fitting | 25mm | 25 |
| RTF-3245 | 32mm 45° Fitting | 32mm | 10 |
| RTF-4045 | 40mm 45° Fitting | 40mm | 5 |
| RTF-5045 | 50mm 45° Fitting | 50mm | 2 |
| RTF-6345 | 63mm 45° Fitting | 63mm | 1 |

90° BRASS FITTINGS



| RTF-1690 | 16mm 90° Fitting | 16mm | 25 |
|----------|------------------|------|----|
| RTF-2090 | 20mm 90° Fitting | 20mm | 25 |
| RTF-2590 | 25mm 90° Fitting | 25mm | 25 |
| RTF-3290 | 32mm 90° Fitting | 32mm | 10 |
| RTF-4090 | 40mm 90° Fitting | 40mm | 5 |
| RTF-5090 | 50mm 90° Fitting | 50mm | 2 |
| RTF-6390 | 63mm 90° Fitting | 63mm | 1 |

NICKEL PLATED FITTINGS









Standards: ANZEx 08-3020X DIP A21 IP66Metal FittingsMetric ThreadsIP66

STRAIGHT METAL FITTINGS



| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|------------|-----------------------|-------------|----------|
| RTFM-16 | 16mm Straight Fitting | 16mm | 25 |
| RTFM-16/20 | 16mm Straight Fitting | 20mm | 25 |
| RTFM-20 | 20mm Straight Fitting | 20mm | 25 |
| RTFM-25 | 25mm Straight Fitting | 25mm | 25 |
| RTFM-32 | 32mm Straight Fitting | 32mm | 10 |
| RTFM-40 | 40mm Straight Fitting | 40mm | 5 |
| RTFM-50 | 50mm Straight Fitting | 50mm | 2 |
| RTFM-63 | 63mm Straight Fitting | 63mm | 1 |

45° METAL FITTINGS



| RTFM-1645 | 16mm 45° Fitting | 16mm | 25 |
|--------------|------------------|------|----|
| RTFM-16/2045 | 16mm 45° Fitting | 20mm | 25 |
| RTFM-2045 | 20mm 45° Fitting | 20mm | 25 |
| RTFM-2545 | 25mm 45° Fitting | 25mm | 25 |
| RTFM-3245 | 32mm 45° Fitting | 32mm | 10 |
| RTFM-4045 | 40mm 45° Fitting | 40mm | 5 |
| RTFM-5045 | 50mm 45° Fitting | 50mm | 2 |
| RTFM-6345 | 63mm 45° Fitting | 63mm | 1 |

90° METAL FITTINGS



| , | | | |
|---|------------------|------|----|
| RTFM-1690 | 16mm 90° Fitting | 16mm | 25 |
| RTFM-16/2090 | 16mm 90° Fitting | 20mm | 25 |
| RTFM-2090 | 20mm 90° Fitting | 20mm | 25 |
| RTFM-2590 | 25mm 90° Fitting | 25mm | 10 |
| RTFM-3290 | 32mm 90° Fitting | 32mm | 5 |
| RTFM-4090 | 40mm 90° Fitting | 40mm | 4 |
| RTFM-5090 | 50mm 90° Fitting | 50mm | 2 |
| RTFM-6390 | 63mm 90° Fitting | 63mm | 2 |

ACCESSORIES

FERRULES



| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|---------|----------------------|-------------|----------|
| LT-OF | 16mm Conduit Ferrule | | 100 |
| LT-1F | 20mm Conduit Ferrule | | 100 |
| LT-2F | 25mm Conduit Ferrule | | 50 |
| LT-3F | 32mm Conduit Ferrule | | 50 |
| LT-4F | 40mm Conduit Ferrule | | 20 |
| LT-5F | 50mm Conduit Ferrule | | 5 |
| LT-6F | 63mm Conduit Ferrule | | 5 |

LOCKNUTS



| LNB-16N | 16mm Nickel Plated Locknut | 100 |
|---------|----------------------------|-----|
| LNB-20N | 20mm Nickel Plated Locknut | 100 |
| LNB-25N | 25mm Nickel Plated Locknut | 100 |
| LNB-32N | 32mm Nickel Plated Locknut | 50 |
| LNB-40N | 40mm Nickel Plated Locknut | 50 |
| LNB-50N | 50mm Nickel Plated Locknut | 25 |
| LNB-63N | 63mm Nickel Plated Locknut | 20 |

FLAME PROOF EXD FITTINGS



| FLC-20 | 20mm Barrier Fitting | 20mm | As Required |
|---------|-------------------------------|--------|-------------|
| FLC-25 | 25mm Barrier Fitting | 25mm | As Required |
| FLC-075 | ¾" BSP Female Barrier Fitting | ¾" BSP | As Required |
| FLC-100 | 1" BSP Female Barrier Fitting | 1" BSP | As Required |

Standards: ANZEx 09-3018 Exd IIB DIP IP65

SEALSAFE FLEXIBLE PVC CONDUIT & FITTINGS



- Standards: AS/NZ 2053.8 ANZEx 09-3018 Exd IIB DIP IP65
- | FC Fibre braided conduit
- A synthetic reinforcing braid woven over a flexible PVC inner core with an Orange flame retardant PVC jacket.

FLEXIBLE CONDUIT

| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|---------|---------------------|-------------|----------|
| FC-16 | 20mm Orange Conduit | | 30M |
| FC-19 | 25mm Orange Conduit | | 30M |

EXD CONDUIT FITTINGS



| FHC-2003 | 20mm Male Barrier Fitting | 20mm | 1 |
|----------|---------------------------|------|---|
| FHC-2503 | 25mm Male Barrier Fitting | 25mm | 1 |

Standards: ANZEx 09-3018 Exd IIB DIP IP65



| FHC-075 | ¾" BSP Female Fitting | ¾" BSP | 1 |
|---------|-----------------------|--------|---|
| FHC-100 | 1" BSP Female Fitting | 1" BSP | 1 |

Standards: ANZEx 09-3018 Exd IIB DIP IP65



ZONE 21 (DIP) CONDUIT FITTINGS

| FHC-2002 | 20mm Male Fitting | 20mm | 1 |
|----------|-------------------|------|---|
| FHC-2502 | 25mm Male Fitting | 25mm | 1 |

PLIABLE STAINLESS STEEL CONDUIT & FITTINGS



Standards: IEC 61386-1: 2008 IEC 61386-22: 2002

304 Stainless Steel core

Flame retardant due to no PVC jacket

UV resistant

IP 66/68

Temperature range -60°C to +200°C using silicon "O" rings

Sizes 16mm - 63mm

PLIABLE STAINLESS STEEL CONDUIT

| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|---------|-----------------------|-------------|----------|
| RTS-16 | 16mm Straight Conduit | 16mm | 20M |
| RTS-20 | 20mm Straight Conduit | 20mm | 20M |
| RTS-25 | 25mm Straight Conduit | 25mm | 20M |
| RTS-32 | 32mm Straight Conduit | 32mm | 20M |
| RTS-40 | 40mm Straight Conduit | 40mm | 10M |
| RTS-50 | 50mm Straight Conduit | 50mm | 10M |
| RTS-63 | 63mm Straight Conduit | 63mm | 10M |

STRAIGHT NICKEL PLATED BRASS FITTINGS



| RTSF-16B | 16mm Straight Conduit Fitting | 16mm | 36 |
|----------|-------------------------------|------|----|
| RTSF-20B | 20mm Straight Conduit Fitting | 20mm | 20 |
| RTSF-25B | 25mm Straight Conduit Fitting | 25mm | 15 |
| RTSF-32B | 32mm Straight Conduit Fitting | 32mm | 15 |
| RTSF-40B | 40mm Straight Conduit Fitting | 40mm | 9 |
| RTSF-50B | 50mm Straight Conduit Fitting | 50mm | 2 |
| RTSF-63B | 63mm Straight Conduit Fitting | 63mm | 2 |

STRAIGHT STAINLESS STEEL FITTINGS



| RTSF-16S | 16mm Straight Conduit Fitting | 16mm | 36 |
|----------|-------------------------------|------|----|
| RTSF-20S | 20mm Straight Conduit Fitting | 20mm | 20 |
| RTSF-25S | 25mm Straight Conduit Fitting | 25mm | 15 |
| RTSF-32S | 32mm Straight Conduit Fitting | 32mm | 15 |
| RTSF-40S | 40mm Straight Conduit Fitting | 40mm | 9 |
| RTSF-50S | 50mm Straight Conduit Fitting | 50mm | 2 |
| RTSF-63S | 63mm Straight Conduit Fitting | 63mm | 2 |

Note: 316 Stainless Steel Core Conduit available on request

NYLON CONDUIT

PA6 POLYAMIDE NYLON CONDUIT



Material: Polyamide 6

Temp Rating: -40°C to +115°C (Intermittent to +150°C)

IP68

Flame Retardant: HB UL 94 Self Extinguishing (FMVSS)

Halogen free, free of phosphor and cadmium

UV Resistant

Colours: black and grey



| PART NO | DESCRIPTION | I.D. | O.D. | MIN BENDING RADIUS | PACK QTY |
|------------|-------------------------------------|---------|---------|--------------------------|----------|
| RTN-1250-B | Ramtight 12mm PA6 Polyamide Conduit | 10.00mm | 13.00mm | 15mm | 50M |
| RTN-1650-B | Ramtight 16mm PA6 Polyamide Conduit | 12.00mm | 15.80mm | 22mm | 50M |
| RTN-2050-B | Ramtight 20mm PA6 Polyamide Conduit | 16.50mm | 21.20mm | 35mm | 50M |
| RTN-2550-B | Ramtight 25mm PA6 Polyamide Conduit | 23.00mm | 28.50mm | 45mm | 50M |
| RTN-3250-B | Ramtight 32mm PA6 Polyamide Conduit | 29.00mm | 34.50mm | 50mm | 50M |
| RTN-4025-B | Ramtight 40mm PA6 Polyamide Conduit | 36.00mm | 42.50mm | 80mm | 25M |
| RTN-5025-B | Ramtight 50mm PA6 Polyamide Conduit | 48.00mm | 54.50mm | 100mm | 25M |

PA6 POLYAMIDE EXTRA LOW FIRE HAZARD NYLON CONDUIT (VO UL 94)

| Material: Polyamide 6

UL VO Temp Rating

Temp Rating: -40°C to +115°C (Intermittent to +150°C)

IP68



Halogen free, free of phosphor and cadmium

UV Resistant

Colours: black and grey



| RTNVO-1250-B | Ramtight 12mm PA6 VO Polyamide Conduit | 10.00mm | 13.00mm | 15mm | 50M |
|--------------|--|---------|---------|-------|-----|
| RTNVO-1650-B | Ramtight 16mm PA6 VO Polyamide Conduit | 12.00mm | 15.80mm | 22mm | 50M |
| RTNVO-2050-B | Ramtight 20mm PA6 VO Polyamide Conduit | 16.50mm | 21.20mm | 35mm | 50M |
| RTNVO-2550-B | Ramtight 25mm PA6 VO Polyamide Conduit | 23.00mm | 28.50mm | 45mm | 50M |
| RTNVO-3250-B | Ramtight 32mm PA6 VO Polyamide Conduit | 29.00mm | 34.50mm | 50mm | 50M |
| RTNVO-4025-B | Ramtight 40mm PA6 VO Polyamide Conduit | 36.00mm | 42.50mm | 80mm | 25M |
| RTNVO-5025-B | Ramtight 50mm PA6 VO Polyamide Conduit | 48.00mm | 54.50mm | 100mm | 25M |

PA6 POLYAMIDE LOW FIRE HAZARD NYLON CONDUIT (V2 UL 94)

Material: Polyamide 6

UL V2 Temp Rating

Temp Rating: -40°C to +115°C (Intermittent to +150°C)

IP68

- | Flame Retardant: Self Extinguishing (EN 50086-1)
- Halogen free, free of phosphor and cadmium

UV Resistant

Colours: black and grey



| RTNV2-12-B | Ramtight 12mm PA6 V2 Polyamide Conduit | 10.00mm | 13.00mm | 15mm | 50M |
|------------|--|---------|---------|-------|-----|
| RTNV2-16-B | Ramtight 16mm PA6 V2 Polyamide Conduit | 12.00mm | 15.80mm | 22mm | 50M |
| RTNV2-20-B | Ramtight 20mm PA6 V2 Polyamide Conduit | 16.50mm | 21.20mm | 35mm | 50M |
| RTNV2-25-B | Ramtight 25mm PA6 V2 Polyamide Conduit | 23.00mm | 28.50mm | 45mm | 50M |
| RTNV2-32-B | Ramtight 32mm PA6 V2 Polyamide Conduit | 29.00mm | 34.50mm | 50mm | 50M |
| RTNV2-40-B | Ramtight 40mm PA6 V2 Polyamide Conduit | 36.00mm | 42.50mm | 80mm | 25M |
| RTNV2-50-B | Ramtight 50mm PA6 V2 Polyamide Conduit | 48.00mm | 54.50mm | 100mm | 25M |



- | Material: Polyamide 66
- Temp Rating: -40°C to +115°C (Intermittent to +150°C),
- IP66, IP68 with flat sealing ring
- Halogen free, free of phosphor and cadmium
- Flame Retardant: Self Extinguishing (EN 50086-1)
- UV Resistant
- Complete with Locknut
- Colours: black and grey

STRAIGHT NYLON METRIC FITTING



| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|----------|--------------------------------------|-------------|----------|
| RTFN-10B | 10mm Ramtight Straight Nylon Fitting | 10mm | 25 |
| RTFN-12B | 12mm Ramtight Straight Nylon Fitting | 12mm | 25 |
| RTFN-16B | 16mm Ramtight Straight Nylon Fitting | 16mm | 25 |
| RTFN-20B | 20mm Ramtight Straight Nylon Fitting | 20mm | 25 |
| RTFN-25B | 25mm Ramtight Straight Nylon Fitting | 25mm | 10 |
| RTFN-32B | 32mm Ramtight Straight Nylon Fitting | 32mm | 5 |
| RTFN-40B | 40mm Ramtight Straight Nylon Fitting | 40mm | 5 |
| RTFN-50B | 50mm Ramtight Straight Nylon Fitting | 50mm | 5 |

90° NYLON METRIC FITTING



| RTFN-1090B | 10mm Ramtight 90° Nylon Fitting | 10mm | 25 |
|------------|---------------------------------|------|----|
| RTFN-1290B | 12mm Ramtight 90° Nylon Fitting | 12mm | 25 |
| RTFN-1690B | 16mm Ramtight 90° Nylon Fitting | 16mm | 25 |
| RTFN-2090B | 20mm Ramtight 90° Nylon Fitting | 20mm | 25 |
| RTFN-2590B | 25mm Ramtight 90° Nylon Fitting | 25mm | 10 |
| RTFN-3290B | 32mm Ramtight 90° Nylon Fitting | 32mm | 5 |
| RTFN-4090B | 40mm Ramtight 90° Nylon Fitting | 40mm | 5 |
| RTFN-5090B | 50mm Ramtight 90° Nylon Fitting | 50mm | 5 |

45° NYLON METRIC FITTING



| RTFN-2045B | 20MM Ramtight 45° Nylon Fitting | 20MM | 25 |
|------------|---------------------------------|------|----|
| RTFN-2545B | 25MM Ramtight 45° Nylon Fitting | 25MM | 10 |
| RTFN-3245B | 32MM Ramtight 45° Nylon Fitting | 32MM | 5 |
| RTFN-4045B | 40MM Ramtight 45° Nylon Fitting | 40MM | 5 |
| RTFN-5045B | 50MM Ramtight 45° Nylon Fitting | 50MM | 5 |

STRAIGHT NYLON METRIC FITTING



| PART NO | DESCRIPTION | THREAD SIZE | CONDUIT SIZE | PACK QTY |
|-----------|--------------------------------------|-------------|--------------|----------|
| RTFN-PG7 | PG7 Ramtight Straight Nylon Fitting | PG7 | 10mm | 25 |
| RTFN-PG9 | PG9 Ramtight Straight Nylon Fitting | PG9 | 12mm | 25 |
| RTFN-PG11 | PG11Ramtight Straight Nylon Fitting | PG11 | 16mm | 25 |
| RTFN-PG16 | PG16 Ramtight Straight Nylon Fitting | PG16 | 20mm | 25 |
| RTFN-PG21 | PG21 Ramtight Straight Nylon Fitting | PG21 | 25mm | 10 |
| RTFN-PG29 | PG29 Ramtight Straight Nylon Fitting | PG29 | 32mm | 5 |
| RTFN-PG36 | PG36 Ramtight Straight Nylon Fitting | PG36 | 40mm | 5 |
| RTFN-PG48 | PG48 Ramtight Straight Nylon Fitting | PG48 | 50mm | 5 |

90° NYLON PG FITTING



| RTFN-PG790 | PG7 Ramtight 90 Degree Nylon Fitting | PG7 | 10mm | 25 |
|-------------|---------------------------------------|------|------|----|
| RTFN-PG990 | PG9 Ramtight 90 Degree Nylon Fitting | PG9 | 12mm | 25 |
| RTFN-PG1190 | PG11 Ramtight 90 Degree Nylon Fitting | PG11 | 16mm | 25 |
| RTFN-PG1690 | PG16 Ramtight 90 Degree Nylon Fitting | PG16 | 20mm | 25 |
| RTFN-PG2190 | PG21 Ramtight 90 Degree Nylon Fitting | PG21 | 25mm | 10 |
| RTFN-PG2990 | PG29 Ramtight 90 Degree Nylon Fitting | PG29 | 32mm | 5 |
| RTFN-PG3690 | PG36 Ramtight 90 Degree Nylon Fitting | PG36 | 40mm | 5 |
| RTFN-PG4890 | PG48 Ramtight 90 Degree Nylon Fitting | PG48 | 50mm | 5 |

45° NYLON PG FITTING



| RTFN-PG1645 | PG16 Ramtight 90 Degree Nylon Fitting | PG16 | 20mm | 25 |
|-------------|---------------------------------------|------|------|----|
| RTFN-PG2145 | PG21 Ramtight 90 Degree Nylon Fitting | PG21 | 25mm | 10 |
| RTFN-PG2945 | PG29 Ramtight 90 Degree Nylon Fitting | PG29 | 32mm | 5 |
| RTFN-PG3645 | PG36 Ramtight 90 Degree Nylon Fitting | PG36 | 40mm | 5 |
| RTFN-PG4845 | PG48 Ramtight 90 Degree Nylon Fitting | PG48 | 50mm | 5 |

COUPLINGS



| RTCN-10 | 10mm Coupling | 25 |
|---------|---------------|----|
| RTCN-12 | 12mm Coupling | 25 |
| RTCN-16 | 16mm Coupling | 25 |
| RTCN-20 | 20mm Coupling | 25 |
| RTCN-25 | 25mm Coupling | 10 |
| RTCN-32 | 32mm Coupling | 5 |
| RTCN-40 | 40mm Coupling | 5 |
| RTCN-50 | 50mm Coupling | 5 |

T-FITTING



| PART NO | DESCRIPTION | PACK QTY |
|---------|----------------|----------|
| RTTN-20 | 20mm T-Fitting | 10 |
| RTTN-25 | 25mm T-Fitting | 5 |
| RTTN-32 | 32mm T-Fitting | 5 |

Y-FITTING



| PART NO | DESCRIPTION | PACK QTY |
|---------|------------------|----------|
| RTYN-12 | 12mm Y - Fitting | 10 |
| RTYN-16 | 16mm Y - Fitting | 10 |
| RTYN-20 | 20mm Y - Fitting | 10 |
| RTYN-25 | 25mm Y - Fitting | 10 |

PCLAMPS



| RTPN-10 | 10mm P Clamp | M4 | 25 |
|---------|--------------|----|----|
| RTPN-12 | 12mm P Clamp | M4 | 25 |
| RTPN-16 | 16mm P Clamp | M4 | 25 |
| RTPN-20 | 20mm P Clamp | M4 | 25 |
| RTPN-25 | 25mm P Clamp | M5 | 10 |
| RTPN-32 | 32mm P Clamp | M5 | 5 |
| RTPN-40 | 40mm P Clamp | M6 | 5 |
| RTPN-50 | 50mm P Clamp | M6 | 5 |

MOUNTING BRACKETS



| RTMN-10B | 10mm Mounting Bracket | 4.2mm | 25 |
|----------|-----------------------|-------|----|
| RTMN-12B | 12mm Mounting Bracket | 4.2mm | 25 |
| RTMN-16B | 16mm Mounting Bracket | 4.2mm | 25 |
| RTMN-20B | 20mm Mounting Bracket | 4.2mm | 25 |
| RTMN-25B | 25mm Mounting Bracket | 4.2mm | 10 |
| RTMN-32B | 32mm Mounting Bracket | 4.2mm | 5 |
| RTMN-40B | 40mm Mounting Bracket | 4.2mm | 5 |
| RTMN-50B | 50mm Mounting Bracket | 4.2mm | 5 |

METRIC NYLON LOCKNUTS



| RTLN-10B | 10mm Nylon LockNut | 10mm | 25 |
|----------|--------------------|------|----|
| RTLN-12B | 12mm Nylon LockNut | 12mm | 25 |
| RTLN-16B | 16mm Nylon LockNut | 16mm | 25 |
| RTLN-20B | 20mm Nylon LockNut | 20mm | 25 |
| RTLN-25B | 25mm Nylon LockNut | 25mm | 10 |
| RTLN-32B | 32mm Nylon LockNut | 32mm | 5 |
| RTLN-40B | 40mm Nylon LockNut | 40mm | 5 |
| RTLN-50B | 50mm Nylon LockNut | 50mm | 5 |

P.G. NYLON LOCKNUTS



| PART NO | DESCRIPTION | THREAD SIZE | PACK QTY |
|------------|--------------------|-------------|----------|
| RTLN-PG7B | PG7 Nylon LockNut | PG7 | 25 |
| RTLN-PG9B | PG9 Nylon LockNut | PG9 | 25 |
| RTLN-PG11B | PG11 Nylon LockNut | PG11 | 25 |
| RTLN-PG16B | PG16 Nylon LockNut | PG16 | 25 |
| RTLN-PG21B | PG21 Nylon LockNut | PG21 | 10 |
| RTLN-PG29B | PG29 Nylon LockNut | PG29 | 5 |
| RTLN-PG36B | PG36 Nylon LockNut | PG36 | 5 |
| RTLN-PG48B | PG48 Nylon LockNut | PG48 | 5 |

END SLEEVES



| RTES-12 | 12mm End Sleeve | 12mm | As Required |
|---------|-----------------|------|-------------|
| RTES-16 | 16mm End Sleeve | 16mm | As Required |
| RTES-20 | 20mm End Sleeve | 20mm | As Required |
| RTES-25 | 25mm End Sleeve | 25mm | As Required |
| RTES-32 | 32mm End Sleeve | 32mm | As Required |
| RTES-40 | 40mm End Sleeve | 40mm | As Required |
| RTES-50 | 50mm End Sleeve | 50mm | As Required |



OUR LOCATIONS

National footprint with strategic local stockholdings.

APS Industrial is headquartered in Melbourne and in addition has a nationa network of offices in Adelaide, Perth, Sydney and Brisbane supported by strategic local stockholdings and expert technical and application knowledge.

apsindustrial.com.au

CONNECT WITH US

f in

✓

MELBOURNE

5-7 Corporate Ave, Rowville, Melbourne VIC 3178

Ph: (03) 8514 3500 Fax: (03) 8514 3510

Sales: 1300 309 303 Sales Fax: 1300 309 308

SYDNEY

Unit P1, 10-16 South Street Rydalmere, Sydney NSW 2116

Ph: (02) 8898 6200 Fax: (02) 8898 6202

Sales: 1300 309 303 Sales Fax: 1300 309 308

BRISBANE

Unit 2, 5 Breene Place Morningside, Brisbane QLD 4170

Ph: (07) 3899 1322 Fax: (07) 3899 1422

Sales: 1300 309 303 Sales Fax: 1300 309 308

ADELAIDE

13-15 Shepley Avenue Panorama, Adelaide SA 5041

Ph: (08) 8111 5100 Fax: (08) 8111 5105

Sales: 1300 309 303 Sales Fax: 1300 309 308

PERTH

56 Millrose Drive, Malaga, Perth WA 6090

Ph: (08) 9249 9155 Fax: (08) 9249 9418

Sales: 1300 309 303 Sales Fax: 1300 309 308