

SIEMENS

SIMATIC S7-1200

STARTER KIT



EDGE
INTEGRATION



INTEGRATED
SAFETY



SCALABLE
DESIGN



SIMATIC S7-1200 Starter Kit Special Offer

Now is the perfect time to take advantage of SIMATIC S7-1200 controllers!

Enhance your automation systems with cutting-edge technology that maximises efficiency and unlocks limitless possibilities.

It's never been easier to get started!

Unleash the power of SIMATIC S7-1200 Starter Kits from APS. Streamline your automation tasks effortlessly. Tailored for the Australian market, these kits offer flexibility, efficiency, and seamless integration with TIA Portal software and HMI Panels. Elevate your automation game today!



Enjoy up to **70% in savings** on starter kit & HMI add-ons!

BASIC STARTER KIT

SIMATIC S7-1200 Starter Kit consisting of:

CPU 1212 FC | Power Module | Industrial Ethernet TP Cord
SIMATIC STEP 7 Basic V20 | SIMATIC Standard Mounting Rail

FREE
1 DAY
TRAINING



FREE BACK TO BASICS TRAINING INCLUDED WITH EVERY STARTER KIT PURCHASED.
STARTER KIT DOES NOT INCLUDE INSTALLATION OR COMMISSIONING.

*** *To complete your kit, select from the below HMI or drive add-ons:* ***

SIMATIC HMI

HMI OPTION 1

SIMATIC HMI MTP400, Unified Basic Panel, touch operation, 4" widescreen TFT display, 16 million colours, PROFINET interface, configurable as of WinCC Unified Basic V20, contains open-source software, which is provided free of charge.



HMI OPTION 2

SIMATIC HMI MTP700, Unified Basic Panel, touch operation, 7" widescreen TFT display, 16 million colours, PROFINET interface, configurable as of WinCC Unified Basic V20, contains open-source software, which is provided free of charge.



HMI OPTION 3

SIMATIC HMI MTP1000, Unified Basic Panel, touch operation, 10" widescreen TFT display, 16 million colours, PROFINET interface, configurable as of WinCC Unified Basic V20, contains open-source software, which is provided free of charge.



SINAMICS DRIVE

DRIVE OPTION 4

SINAMICS G120C rated power 0,55kw with 150% overload for 3 sec 3AC380-480V +10/-20% 47-63HZ integrated filter class a I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO safe torque off integrated fieldbus: profinet-pn protection: IP20/ UL open type size: FSAA 173x73x178(HxWxD) external 24V.



***ONLY VALID WITH KIT**